

#### TECHNICAL DATA SHEET

Note: For safe, efficient blasting, read and follow the owner's manual and seek training for everyone who will use this equipment.

### **Purpose**

Two-braid hose is used in industrial settings where external scuffing is expected. It can be used with all common blast media. Clemco 2-braid blast hose has a durable outer casing and is more flexible than 4-ply hose.

### **Description of Operation**

Clemco 2-braid blast hose accepts properly sized couplings and nozzle holders. The coupled hose can attach to any blast machine rated at up to 150 psi. Two-braid hose is widely used in shipyards and railyards because it stands up to external abrasions from being dragged about the blast site.

For applications where 2-braid blast hoses are used (for their more durable outer casing), a 10 to 15 foot length of Clemco Supa hose can be connected as the last section before the nozzle. This whip hose is easier for the operator to bend and manuever.

# **Advantages**

- More durable outer casing than Supa hose
- Inner tube wall of SBR rubber treated with static-dissipating compound, up to 5/16-inch thick depending upon hose
- Two-layer outer casing of cloth and rubber-impregnated fiber winding
- Casing is pin-pricked to prevent formation of air pockets between
- More flexible than 4-ply blast hose

ISO 9001-2000 certified. Clemco is committed to continuous product improvement. Specifications are subject to change without notice.

# **Description**

Durable, reinforced 2-braid blast hose, rated at 175 psi working pressure.



#### **Related Clemco Literature**

Description	Stock No.
Contractor Series Catalog	21385
Abrasive Blasting	
Safety Practices	22090
Blast Off 2	09294
Safety Cable TDS	21970

## **Options and Accessories**

For 1/2-inch 2-braid CHE-1/2 nylon nozzle holder, contractor thread ......00577 CQA-1/2 aluminum coupling ......00599 For 3/4-inch 2-braid NHP-1 nylon nozzle holder, contractor thread ......04106 CQP-1 nylon coupling......08412 HEP-1 nylon nozzle holder, fine thread ......07720 For 1-inch 2-braid NHP-2 nylon nozzle holder, contractor thread ......04127 CQP-2 nylon coupling......21711 HEP-2 nylon nozzle holder, fine thread ......07721


#### For 1-1/4 -inch 2-braid

NHP-3 nylon nozzle holder, contractor thread ......04128 CQP-3 nylon coupling......08414 HEP-3 nylon nozzle holder,

fine thread ......07722

# Blast Hose, 2-Braid

Stock No. 23750, 23751, 23752, 23753, 23754, 23755, 23756



Standard 2-Braid	
Description	Stock No.
1/2" ID x 1-13/16" OD x 25'	23750
1/2" ID x 1-13/16" OD x 50'	23751
3/4" ID x 1-5/16" OD x 25'	23752
3/4" ID x 1-5/16" OD x 50'	23753
1" ID x 1-7/8" OD x 25'	23754
1" ID x 1-7/8" OD x 50'	23755
1-1/4" ID x 2-3/32" OD x 50'.	23756

#### Color - Green Ships coiled and shrink wrapped.

•	
Stock No.	Weight
23750	12 lbs
23751	26 lbs
23752	17 lbs
23753	35 lbs
23754	25 lbs
23755	51 lbs
23756	62 lbs

Description	Stock No.
Blast hose safety cable	15013

Authorized Distributor: