

SAFETY DATA SHEET VF-M Ceramic Media

1. PRODUCT AND COMPANY IDENTIFICATION					
Product Code: Product Name: Company Name:	VFMCM VF-M Ceramic Media Vibra Finish Co. 8411 Seward Road Hamilton, OH 45011	Phone Number: +1 (800)253-1941			
Web site address:	www.vibrafinish.com Chemtrec	1 (800) 424 0200			
Emergency Contact:		+1 (800)424-9300			
2. HAZARDS IDENTIFICATION					
GHS Signal Word: GHS Hazard Phrases: GHS Precaution Phrases:	None No phrases apply. No phrases apply.				
GHS Response Phrases: GHS Storage and Disposal Phrases:	No phrases apply. No phrases apply.				
Potential Health Effects (Acute and Chronic):	No hazard expected in normal industrial use.				
Inhalation:	This product should not be used dry. Airborne concentrations of dusts or mists may cause irritation to the upper respiratory tract and lungs. Respirable crystalline silica is an IARC and NTP probable carcinogen based on animal studies.				
Skin Contact:	Handling this material with bare hands can cause abrasions.				
Eye Contact:	It is possible for small fragments of this material or the work piece to be propelled from the work area and strike the eye. This product should not be used dry. Airborne concentrations of dusts or mists may cause irritation to the eyes.				
Ingestion:	Not a likely route of exposure. May be harmful if swallowed.				
Additional Hazards Information	This product, as supplied, is should not be used dry.	not classified as hazardous under OSHA. This product			
3. COMPOSITION/INFORMATION ON INGREDIENTS					
CAS # Hazardous Com	ponents (Chemical Name)	Concentration			

1332-58-7	Kaolin	40 - 50 %
1344-28-1	Aluminum oxide	10 - 20 %
68476-25-5	Feldspar	10 - 20 %
7631-86-9	Silica	10 - 20 %
14807-96-6	Talcum	0 - 10 %
13983-17-0	Wollastonite	0 - 10 %

Additional Composition Information:

This product composition information is provided in the unlikely event that a dust is generated during the use of this product. In the material as supplied, these components are not readily available to create a respiration hazard.



4. FIRST AID MEASURES				
Emergency and First Aid Procedures:	None that are directly attributable to normal use of this material.			
In Case of Inhalation:	If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.			
In Case of Skin Contact:	Wash off with soap and plenty of water. Get medical aid if irritation develops and persists.			
In Case of Eye Contact:	Flush eyes with water as a precaution. If eye irritation persists, get medical advice/attention.			
In Case of Ingestion:	Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.			
Signs and Symptoms Of Exposure:	The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. This material, as supplied, is significantly larger than 3-4 um and does not pose as respiration hazard unless the material is used in a manner that generates a dust. This material should not be used dry.			
Note to Physician:	Treat symptomatically and supportively. Show this safety data sheet to the doctor in attendance.			
	5. FIRE FIGHTING MEASURES			
Flash Pt:	NA Method Used: Not Applicable			
Explosive Limits:	LEL: No data. UEL: No data.			
Autoignition Pt:	NA			
Suitable Extinguishing Media	a: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.			
Fire Fighting Instructions:	The product itself does not burn. As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH approved (or equivalent), and full protective gear.			
Flammable Properties and Hazards:	None known.			
Hazardous Combustion Products:	None known.			
6. ACCIDENTAL RELEASE MEASURES				
Protective Precautions, Protective Equipment and Emergency Procedures:	Use proper personal protective equipment as indicated in Section 8.			
Environmental Precautions:	Do not let product enter storm drains, storm sewers, watersheds or water systems unless authorized.			
Steps To Be Taken In Case Material Is Released Or Spilled:	Use proper personal protective equipment as indicated in Section 8. Avoid dust formation. Avoid breathing dust. Collect for reuse or disposal if contaminated with foreign matter.			
7. HANDLING AND STORAGE				
Precautions To Be Taken in Handling:	Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Do not ingest or inhale. Provide appropriate exhaust ventilation at places where dust is formed. This product should not be used dry. Material is heavy, use proper lifting techniques.			
Precautions To Be Taken in Storing:	Store in a dry place. Store in well-ventilated place.			
Other Precautions:	Keep out of reach of children. Handle in accordance with good industrial hygiene and safety practices.			



SAFETY DATA SHEET VF-M Ceramic Media

	Partial Chemical	Name	OSHA TWA	ACGIH TWA	Other Limits	
1332-58-7	Kaolin		PEL: 15 (dust); 5 (resp.) mg/m3	TLV: 2 mg/m3 (E,R)	No data.	
1344-28-1	Aluminum oxide		PEL: 15 (dust); 5 (resp.) mg/m3	TLV: 10 mg/m3 (E)	No data.	
68476-25-5	Feldspar		No data.	No data.	No data.	
7631-86-9	Silica		PEL: 80 mg/m3 / %SiO2	No data.	No data.	
14807-96-6	Talcum		PEL: 706 ppm/20 mppcf	TLV: 2 mg/m3 (non-asbestos)	No data.	
13983-17-0	Wollastonite		No data.	No data.	No data.	
Respiratory I Specify Type		Use a NIOSH/MSHA approved respirator where dust may be generated.				
Eye Protectio	on:	Safety glasses. W	ear chemical splash gogg	les where there is potent	ial for eye contac	
Protective GI	loves:	Handle with glove				
Other Protec	tive Clothing:	Not required unde	er normal use conditions.			
Engineering		•	tilation should be sufficien		s. Facilities storir	
Ventilation e	-	U U	or utilizing this material should be equipped with an eyewash facility.			
	ic/Maintenance		Handle in accordance with good industrial hygiene and safety practice. Wash hands			
Practices:		before breaks and	at the end of workday.			
	9.	PHYSICAL A	AND CHEMICAL P	ROPERTIES		
Physical States: [] Gas [] Liquid [X] Solid						
••		Appearance: Gray. Solid. Varying size and shape.				
••		Odor: Odorless.				
pH:		NA				
pH: Melting Point	t:	NA NA				
oH: Melting Point Boiling Point	t:	NA NA NA				
oH: Melting Point Boiling Point Flash Pt:	t: ::	NA NA NA NA Method Use	d: Not Applicable			
pH: Melting Point Boiling Point Flash Pt: Evaporation	t: :: Rate:	NA NA NA Ma Method Use				
oH: Melting Point Boiling Point Flash Pt: Evaporation Flammability	t: :: Rate: [,] (solid, gas):	NA NA NA MA Method Use NA No data available				
oH: Melting Point Boiling Point Flash Pt: Evaporation Flammability Explosive Lir	t: :: Rate: / (solid, gas): mits:	NA NA NA Method Use NA No data available LEL: No data.		No data.		
oH: Melting Point Boiling Point Flash Pt: Evaporation Flammability Explosive Lir Vapor Pressu	t: :: Rate: [,] (solid, gas):	NA NA NA MA Method Use NA No data available		No data.		
oH: Melting Point Boiling Point Flash Pt: Evaporation Flammability Explosive Lir Vapor Presso mm Hg):	t: Rate: (solid, gas): mits: ure (vs. Air or	NA NA NA Ma Method Use NA No data available LEL: No data. NA		No data.		
oH: Melting Point Boiling Point Flash Pt: Evaporation Flammability Explosive Lin Vapor Pressu mm Hg): Vapor Densit	t: Rate: (solid, gas): mits: ure (vs. Air or ty (vs. Air = 1):	NA NA NA Method Use NA No data available LEL: No data. NA		No data.		
oH: Melting Point Boiling Point Flash Pt: Evaporation Flammability Explosive Lin Vapor Presso mm Hg): Vapor Densit Specific Grav	t: Rate: (solid, gas): mits: ure (vs. Air or	NA NA NA Method Use NA No data available LEL: No data. NA		No data.		
oH: Melting Point Boiling Point Flash Pt: Evaporation Flammability Explosive Lin Vapor Presso mm Hg): Vapor Densit Specific Grav	t: Rate: (solid, gas): mits: ure (vs. Air or ty (vs. Air = 1): vity (Water = 1):	NA NA NA Method Use NA No data available LEL: No data. NA NA NA		√o data.		
pH: Melting Point Boiling Point Flash Pt: Evaporation Flammability Explosive Lin Vapor Presso mm Hg): Vapor Densit Specific Grav Density: Bulk density	t: Rate: (solid, gas): mits: ure (vs. Air or ty (vs. Air = 1): vity (Water = 1):	NA NA NA Method Use NA No data available LEL: No data. NA NA NA S5 - 90 LB/CF		No data.		
pH: Melting Point Boiling Point Flash Pt: Evaporation Flammability Explosive Lin Vapor Pressu mm Hg): Vapor Densit	t: Rate: (solid, gas): mits: ure (vs. Air or ty (vs. Air = 1): vity (Water = 1): : Water:	NA NA NA Method Use NA No data available LEL: No data. NA NA NA		No data.		



SAFETY DATA SHEET VF-M Ceramic Media

			00			
Octanol/Water Partition Coefficient:	No data.					
Autoignition Pt:	NA					
Decomposition Temperature:	emperature: No data.					
Viscosity:	NA					
	10. ST	ABILITY AND READ	CTIVITY			
Reactivity:	Not reactive at normal temperatures and pressures.					
Stability:	Unstable []	able [] Stable [X]				
Conditions To Avoid - Instability:	None known.	ne known.				
Incompatibility - Materials To Avoid:	None known.	one known.				
Hazardous Decomposition or Byproducts:	None known.	wn.				
Possibility of Hazardous Reactions:	Will occur []] Will not occur [X]				
Conditions To Avoid - Hazardous Reactions:	No data availa	o data available.				
	11. TOXI	COLOGICAL INFO	RMATION			
Toxicological Information:	Teratogenicity Reproductive Mutagenicity: Neurotoxicity: Other Studies Tumorigenic E Other Studies	No information available. : No information available. Effects: No information available. No information available. No information available. : CAS# 1344-28-1: :ffects, TDLo, Intrapleural, R : CAS# 14807-96-6: :ffects, TCLo, Inhalation, Rat	at, 90 mg/kg.			
ritation or Corrosion:This product should not be used dry. Airborne concentrations of dusts or mists may cause irritation to the upper respiratory tract and lungs. Airborne concentrations of or mists may cause irritation to the eyes.Other Studies: CAS# 14807-96-6: Standard Draize Test, Skin, Species: Human, 300ug, 3D.				•		
Symptoms related to Toxicological Characteristics	-	material with bare hands can his material or the work piece		•		
Chronic Toxicological Effects:	The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. This material, as supplied, is significantly larger than 3-4 um and does not pose as respiration hazard unless the material is used in a manner that generates a dust. This material should not be used dry.					
Carcinogenicity/Other Information:	OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. Respirable crystalline silica is an IARC and NTP probable carcinogen based on animal studies.					
Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated	? No		



12. ECOLOGICAL INFORMATION				
General Ecological Information:	Environmental: No information available. Physical: No information available.			
Results of PBT and vPvB assessment:	No data available.			
Persistence and Degradability:	No data available.			
Bioaccumulative Potential:	No data available.			
Mobility in Soil:	No data available.			
	13. DISPOSAL CONSIDERATIONS			
Waste Disposal Method:	Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification. Observe all federal, state, and local environmental regulations.			
14. TRANSPORT INFORMATION				
LAND TRANSPORT (US DOT):			
DOT Proper Shipping Name: Not regulated as a hazardous material. DOT Hazard Class: UN/NA Number:				
15. REGULATORY INFORMATION				

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	- Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
1332-58-7	Kaolin	No	No	No
1344-28-1	Aluminum oxide	No	No	Yes
68476-25-5	Feldspar	No	No	No
7631-86-9	Silica	No	No	No
14807-96-6	Talcum	No	No	No
13983-17-0	Wollastonite	No	No	No
CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists		
1332-58-7	Kaolin	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: Yes		
1344-28-1	Aluminum oxide	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 2891; NY Part 597: No; PA HSL: Yes - E; SC TAP: No; WI Air: No		
68476-25-5	Feldspar	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No		
7631-86-9	Silica	TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No		



14807-96-6 Talcum

13983-17-0 Wollastonite

SAFETY DATA SHEET VF-M Ceramic Media

Page: 6 of 6 Printed: 09/20/2017 Revision: 09/04/2017 Supersedes Revision: 07/01/2014

TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 4203; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: Yes

TSCA: No; CA PROP.65: No; CA TAC, Title 8: Title 8; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No

16. OTHER INFORMATION

Revision Date: Preparer Name: 09/04/2017 Crystal Maira

Hazard Rating System:

Flammability Instability Health NFPA: Special Hazard

Additional Information: Company Policy or Disclaimer: 09/04/2017 Updated sections 2, 10, 11

Vibra Finish company cannot anticipate all conditions which this information and our products, or the products of other manufacturers in combination with our products may be used. We accept no responsibility for results obtained by the application of this information, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of our products, whether alone or in combination with other products.